



Pi9000(UK)S

- ✓ Dual-sensor smoke alarm - includes both ionisation and photoelectric sensors
- ✓ Hush feature allows nuisance alarms to be temporarily silenced (e.g those caused by cooking or steam)
- ✓ Battery operated (9V battery supplied as standard)
- ✓ "Test/Reset Button Tests alarm circuit operation"

Product Description

This dual-sensor alarm has both ionisation and photoelectric sensors and also benefits from the hush feature that allows nuisance alarms (such as cooking or steam) to be temporarily silenced.

At least one smoke alarm should be installed on each level of the home and in areas close to bedrooms. A working smoke alarm provides the earliest possible warning of smoke or fire in the home and can double a person's chance of surviving a house fire. There are many different types of smoke alarms with various features for enhanced usability.

Kidde recommends that for maximum protection both ionisation and photoelectric smoke alarms are installed in the home.

* Ionisation sensing alarms may detect invisible fire particles (associated with fast flaming fires) sooner than photoelectric alarms. Photoelectric alarms may detect visible fire particles (associated with slow smouldering fires) sooner than ionisation alarms.



Order Code	Pi9000(UK)S
Power Supply	Battery operated (9V battery supplied as standard)
Temperature Range	4.4°C to +37.8°C
Humidity Range	Up to 85% Relative Humidity (RH)
Alarm Dimensions	185mm x 185mm x 45mm
Alarm Weight	0.33kg
Approvals	Certified by UL / CE approved
Warranty	5 years
Dimensions (packaged)	215mm x 190mm x 50mm
Weight (packaged)	0.38kg
UPC Barcode	0-047871-099528
Case Quantity	3
Case Dimensions	202mm x 158mm x 296mm
Case Weight	1.2
ITF Outer Code	20047871099522

