



PRODUCT

10LLCO

10-year Carbon Monoxide Alarm



Sealed-in batteries last the life of the alarm

DESCRIPTION

Sleek, lightweight CO alarm with a non-replaceable, sealed-in Lithium battery for ten years of continuous protection – meaning the user never needs to change the battery for the full duration of the alarm’s life.

KEY FEATURES

- **Sealed-in lithium batteries** – will last the full 10-year alarm life without ever needing to be replaced
- **Continuous monitoring** of carbon monoxide
- **Alarm memory** – the red LED will flash every 60 seconds to indicate a CO ‘event’ has occurred
- **Unique water-based Kidde CO Electrochemical Sensor**
- **CO ‘Quick-Test’ feature** – temporarily de-sensitises the CO sensor to allow quick-testing using Kidde approved CO sprays
- **Interrogation feature** – allows peak level, test history to be analysed by Kidde upon arrangement
- **3 LEDs** – Alarm, Operate and Fault
- **End-of-life alarm** alerts user to replace alarm after 10 years of protection
- **Test/Reset button** to allow regular testing of alarm function

WHERE TO USE

This slim, easy-to-use alarm is ideal for use in all living areas and can be installed on a wall or ceiling or used freestanding on a table or shelf. It is also easily portable so can be taken away on holidays.

GENERAL FEATURES

Model	10LLCO
Power Supply	Sealed-in Lithium battery
Temperature Range	0°C to 40°C
Humidity Range	Up to 90% relative humidity (RH) non-condensing
Storage and Transport	-20°C to +60°C and 5–95% relative humidity (RH) non-condensing
Alarm Dimensions	116 x 72 x 40mm
Alarm Weight	140g
Warranty	10 years
Approvals	BSI certified to EN52091-1 CE tested and certified



EN52091-1: 2010
Licence no. KM98848

PRODUCT

10LLCO

10-year Carbon Monoxide Alarm



POWER SOURCE

Sealed-in Lithium battery

SENSOR TYPE

Electrochemical

NOTES

PACKAGED SPECIFICATION

	BOX
Order Code	10LLCOB
Pack Dimensions	76 x 122 x 50mm
Pack Weight	190g
UPC Barcode	0-047871-096343
Case Quantity	3
Case Dimensions	202 x 158 x 296mm
Case Weight	1.1Kg
ITF Outer Code	100-47871-096340

