

()

帅

PRODUCT

i9080 Smoke Alarm

Smoke Alarm with Escape Light

			No. of Control of Cont	
)	DESCRIPTION	Battery-powered smoke alarm with built-in light that helps illuminate your way to safety in the event of an incident – it uses an ionisation sensor to detect fast-flaming fires that can burn combustible materials quickly and without warning.		
,				
	KEY FEATURES	• Built-in emergency escape light designed to guide you to safety through smoke and fire		
		 Combined Test/Hush™ button allows regular testing of alarm function and can be used to temporarily silence nuisance alarms 		
		Battery operation	n – 9V batteries x 2 supplied as standard	
	WHERE TO USE	This easy-to-install battery-powered unit is ideal for use in hallways and on landings where the high intensity escape light can help to highlight the principal escape routes from a smoke-filled building.		
	GENERAL FEATURES	Model	i9080	
		Power Supply	9V batteries x 2 supplied as standard	
		Temperature Range	0°C to + 40°C	
`		Humidity Range	Up to 90% Relative Humidity (RH) non-condensing	
)		Storage and Transport	-20°C to +60°C and 5–95% relative humidity (RH) non-condensing	
		Alarm Dimensions	124 x 124 x 36mm	
		Alarm Weight	270g	
		Warranty	5 years	
		Approvals	LPCB certified to BS EN14604:2005	
			CE tested and certified	
			EN14604: 2005 0832-CPD-1429 LPCB Ref No 904a/08 10	
			EN14604:2005	

